

## **Under Cabinet Hoods**




The FIT system eliminates measuring, cutting and filler strips for a perfect fit every time.\* Fast installation that's simple enough for one person.



1 Attach brackets and prep hood for electrical connection



Position hood and attach to cabinet



**3** Complete electrical connection to the hood




## **Under Cabinet Hoods**

MODEL							
	UXT2030AD	UXT3030AD	UXT4030AD	UXT4130AD	UXT4230AD	UXT5230BD	UXT5530AA
New 2014 model	•	•	•	•	•	•	
Size	30" Traditional	30" Traditional	30" High Performa				
Also available in 36"			UXT4036AD	UXT4136AD	UXT4236AD	UXT5236BD	UXT5536AA
FIT system	•	•	•	•	•	•	
Vertical venting	Exterior	Exterior	Interior	Exterior and Interior	Exterior and Interior	Exterior and Interior	Exterior and Inter
Horizontal venting		Exterior	Interior	Exterior and Interior	Exterior and Interior	Exterior and Interior	Exterior and Inter
Туре	Top venting only	Top and rear venting	Recirculating only	Convertible	Convertible	Convertible	Convertible
DUCT/DAMPER TYPE							
Duct-free		•	•	Optional	Optional	Optional	Optional
7" Round duct	Included	Optional	Optional	Optional	Optional	Optional	Optional
3¼" x 10" Rectangular duct		Included		Included	Included	Included	Included
Dishwasher-safe grease filter	1	1		1	1	1	2 (30") or 3 (36
FEATURES							
Maximum exhaust (CFM)*	190	190		190	225	350	400
Sones*	up to 4.5	up to 4.5		up to 4.5	up to 6.4	up to 7	up to 8
Controls	2-speed, rocker switch	2-speed, rocker switch	2-speed, rocker switch	2-speed, rocker switch	Variable speed, rotary	3-speed, push-button	3-speed, push-button
Fan	Axial	Axial	Axial	Axial	Axial	Axial	Centrifugal
Lighting	75-watt On/Off incandescent	75-watt On/Off incandescent	75-watt On/Off incandescent	75-watt On/Off incandescent	75-watt High/Low/Off incandescent	50-watt High/Low halogen (bulbs included)	50-watt High/Lo halogen (bulbs incl
Recirculation kit/Charcoal filter			Included	Optional	Optional	Optional	Included
California Title 24 compliant	•	•	•			•	•
ACCESSORIES							
Recirculation kit/Charcoal filter			W10355450	W10355450	W10355450	W10369358 / W10386873	W10272068
7" Round damper	Included	W10355451	W10355451	W10355451	W10355451	W10355451	
7" Damper plate	Included	W10388168	W10388168	W10388168	W10388168	W10388168	
Power cord	W10355452	W10355452	W10355452	W10355452	W10355452	W10355452	
DIMENSIONS AND COLORS							
Cutout width	30"	30"	30" / 36"	30"/36"	30" / 36"	30" / 36"	30" / 36"
Minimum mounted height	18"	18"	18"	18"	18"	18"	24"
Height	5"	5"	5"	5"	5"	5"	9"
Width	2915/16"	2915/16"	2915/16" / 3515/16"	2915/16" / 3515/16"	2915/16" / 3515/16"	2915/16" / 3515/16"	2915/16" / 3515/16
Depth	185%"	185%"	185%"	18%"	18%"	185⁄8"	19 %0"
Cutout depth	111/8"	111%"	111%"	111%"	111%"	11 1/8"	12"
Available colors	W B	W B	W**   B**   S	W B S	W <sup>†</sup>   B   S	W <sup>††</sup>   B <sup>††</sup>   S	S

Bold type indicates a step-up feature









<sup>\*</sup>At highest speed. Sone levels of 4.5 are based on vertical 7" round duct installation. 
\*\*UXT4030AD only. †UXT4230AD only. †UXT5230BD only.  $^{\text{-/}\text{m}} @2013. \text{ All rights reserved. Printed in the U.S.A. 12/13. Form No. WC130242}$